

Jan Arthur Anne et al.
USSN: 10/646,507
Filed August 23, 2003

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims

1. (Previously Presented) An electrode arrangement for an electric slag melting furnace comprising a bottom wall and at least one side wall defining a furnace interior, said furnace having vertical electrodes for supply of alternating electric current, said vertical electrodes being intended to be submerged in a liquid slag bath, said electrode arrangement being characterized in that the furnace has at least one side wall contact extending into the furnace interior through a side wall of the furnace.
2. (Currently Amended) Electrode arrangement according to claim 1 5 wherein there are two or more side wall contacts and all the side wall contacts are electrically interconnected.
3. (Currently Amended) Electrode arrangement according to claim 1 5, characterized in that at least three side wall contacts are equally circumferentially spaced around the furnace side wall.
4. (Currently Amended) Electrode arrangement according to claim 1 5, characterized in that the at least one side wall contacts are contact is a carbon bodies body inserted into sealed openings in the side wall of the furnace.

Jan Arthur Aune et al.
USPN: 10/646,507
Filed August 23, 2003

5. (Currently Amended) An electrode arrangement for an electric slag melting furnace comprising a bottom wall and at least one side wall defining a furnace interior, said furnace having vertical electrodes for supply of alternating electric current, said vertical electrodes being intended to be submerged in a liquid slag bath, said electrode arrangement being characterized in that the furnace has at least one side wall contact extending into the furnace interior through a side wall of the furnace where the at least one ~~Electrode arrangement according to claim 1, characterized in that each side wall~~ contact is equipped with means for moving the side wall contact radially into the furnace in order to compensate for wear of the at least one side wall contacts contact.

6. (Currently Amended) Electrode arrangement according to claim 1 5, characterized in that the at least one side wall contacts are contact is hollow and have has means for feeding slag forming components through the hollow ~~contacts contact~~.

7. (Canceled)

8. (Currently Amended) A process for heating a mass of slag in an electric slag smelting furnace comprising a bottom wall and at least one side wall defining a furnace interior, a plurality of vertical electrodes above said interior, and at least one side wall contact extending into said interior, said process comprising passing an alternating electric current from at least one of said vertical electrodes through a mass of slag in said interior and to the at least one of said side wall contacts contact and the at least one side

Jan Arthur Aunc et al.
USSN: 10/646,507
Filed August 23, 2003

wall contact is equipped with means for moving the contact radially into the furnace in order to compensate for wear of the at least one side wall contact.

9. (Canceled)

10. (Currently Amended) The process of claim 8, wherein the at least one of said side wall ~~contacts~~ contact is hollow and defines an opening, said process further comprising feeding slag forming components through said opening into said furnace interior.

11. (Currently Amended) The process of claim 8, wherein said bottom wall includes a lining comprising an electrically insulating refractory material.